



## Three-Phase on/off grid Solar Inverter Three phase ESS hybrid inverter



### Product features:

#### Safe & reliable

Passed IEC/EN 62109-1/-2, IEC/EN 62477-1, IEC/EN 61000-6-1/-6-3, European grid connection: EN50549-1, German grid connection: VDE4105/0124 , UK grid connection: G99, South Africa: NRS097-2-1:2017 test certification.

#### Friendly & flexible

Support diesel generator access.

Support full power discharge, automatic management of battery charge and discharge

#### Economical & practica

It is more economical to support multiple operating modes.

Can be as a UPS for the important loads when power off.



Tel:86-010-87227420 Fax:86-010-85885278  
Email: multifit@multifitele.com  
Website: <http://www.multifitele.com>  
Factory Add: 3/F,JieSi Bldg.,6 Keji West Road,  
Hi-Tech Zone 515041,Shantou,Guangdong,China.



Three-Phase on/off grid Solar Inverter

# MULT8KH3~MULT12KH3

## Technical specification:

Technical specification	MULT8KH3	MULT10KH3	MULT12KH3
<b>Input (PV)</b>			
Max.power(kW)	12	15	18
Max. DC voltage(V)		1,000	
MPPT voltage range(V)		180~850	
Max.input current of single MPPT(A)		13	
MPPT tracker/strings	2/1	2/1	2/1
<b>AC output</b>			
Rated output power(kVA)	8	10	12
Max. output current(A)	12.7	15.9	19.1
Grid voltage/range(V)		400/360~440	
Frequency (Hz)		50 /60	
Power factor		0.8lagging-0.8leading	
THDi		<3%	
AC output topology		3W+N+PE	
<b>Battery</b>			
Battery voltage range(V)		125~600	
Max. charging voltage(V)		600	
Full battery voltage(V)	250	300	350
Rated charge/discharge current(A)	40	40	40
Battery type		lithium /Lead-acid	
Communication Interface		CAN/RS485	
<b>EPS output</b>			
Rated power(kVA)	8.8	11	13.2
Rated output voltage(V)		400	
Max. output current(A)	12.7	15.9	19.1
Rated frequency(Hz)		50 /60	
Automatic switching time(ms)		<20	
THDu		<2%	
Overload capacity		110%, 30S/120%, 10S/150%, 0.02S	
<b>General data</b>			
Battery charge /discharge efficiency	96.6%	96.7%	96.8%
DC Max. efficiency	97.9%	98.2%	98.2%
Europe efficienc	97.2%	97.5%	97.5%
MPPT efficiency	99.5%	99.5%	99.5%
Ingress protection		IP65	
Noise emission(dB)		<35	
Operation temperature		-25℃ ~ 60℃	
Cooling		Natural	
Relative Humidity		0 ~95% (non-condensing)	
Altitude		2,000m (>2,000 Derating)	
Dimensions W * D * H (mm)		530*200*600	
Weight(kg)		29	
Isolation transformer		No	
Self-consumption(W)		<3	
<b>Display and communication</b>			
Display		LCD	
Interface:RS485/Wifi/4G/ CAN/DRM		Yes/Opt /Opt /Yes/Yes	
Safety standard		IEC/EN62109-1/-2, IEC/EN62477-1	
EMC		IEC/EN 61000-6-1, IEC/EN 61000-6-3	
On-grid	Europe: EN50549-1, Germany: VDE4105/0124, UK: G99, South Africa: NRS097-2-1:2017		